



WPD SERIES

CLASSIC LED WALL PACK

- ✓ 5 Year Limited Manufacturers Warranty
- ✓ Rated Operating Temp Of -40° To 113° Fahrenheit
- ✓ DLC & UL Certified
- ✓ Replaces 100-400 Watt Metal Halide
- ✓ 60,000 Hour Rated Lifetime

Nominal Specifications

LifeLux™ STD Rating

Power
30W, 45W, 70W, 90W, 135W

Voltage
100-277V AC

Lumen Output
113 - 117 Lm/W

Color Temperature
3000K, 4000K, 5000K, 6000K

Design Life
60,000 hrs

Beam Angle
Type 5 Wide, Medium, and Narrow

CRI
>80

Power Factor
>0.90

Certifications
DLC, UL

Dimensions
30W-70W - 14.21 x 9.25" x 7.4" - 8.8 lbs
90W-135W - 18" x 9.75" x 8.75" - 13.2 lbs

Applications
Exterior Lighting

Warranty
5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below
Example : USALED-WPD-30W-40K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model WPD	Wattage 30 = 30W 45 = 45W 70 = 70W 90 = 90W 135 = 135W	Color Temperature 40K = 4000K 50K = 5000K	Options EM = Emergency Back-up OS = Occupancy Sensor PC = Photocell

Model #	Wattage	CCT	Nominal Lumen Output
WPD-30	30W	3000K, 4000K, 5000K, 6000K	3,400 lm
WPD-45	45W	3000K, 4000K, 5000K, 6000K	5,200 lm
WPD-70	70W	3000K, 4000K, 5000K, 6000K	8,000 lm
WPD-90	90W	3000K, 4000K, 5000K, 6000K	10,500 lm
WPD-135	135W	3000K, 4000K, 5000K, 6000K	15,500 lm

Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires, placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, ensuring electrical connections are sound, and the photocell is operating correctly.

