



# USALED SLR B

## Solar-Integrated LED

- ✓ UL & DLC Certified
- ✓ 50,000 Hour Rated Lifetime
- ✓ Rotatable Solar Panel
- ✓ High Quality ALuminum Alloy & Di-Cast Aluminum Housing
- ✓ Rated Operating Temperature Of -4° To 140° Fahrenheit

### Nominal Specifications

#### LifeLux™ STD Rating

#### Power

15W, 20W

#### Voltage

18V Solar Panel

#### Lumen Output

150 Lm/W

#### Color Temperature

3500K, 4000K, 4500K, 5000K, 5500K, 6000K

#### Design Life

50,000 hrs

#### CRI

>70

#### Power Factor

>0.90

#### Warranty

3 Year Manufacturers Limited Warranty

#### Certifications

UL, DLC

#### Dimensions

25.8" x 11.7" x 11.0" (Fixture)

15W - 26.6" x 23.3" - 35.3 lbs (Panel)

20W - 32.8" x 28.7" - 44.1 lbs (Panel)

#### Mounting Height

13-20'

### ORDERING DATA: Per chart below

Example: USALED-SLR-B-24-15-30K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model SLR B	Panel Width 24 = 24" 26 = 26" 30 = 30"	Wattage 15 = 15W 20 = 20W	Color Temperature 3000K 3500K 4000K 4500K 5000K 5500K 6000K 6500K

Model #	Wattage	CCT	Nominal Lumen Output
USALED-SLR B-15	15W	3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K, 6500K	2,260 lm
USALED-SLR B-20	20W	3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K, 6500K	3,000 lm

### Installation Summary: ( Detailed Instructions provided with Product)

- 1) Set the mounting pole to the appropriate height.
- 2) Locate the wires coming out of the fixture, locating the corresponding wires on the solar panel.
- 3) Connect the corresponding wires and secure as necessary.
- 4) Secure the fixture to the top of the pole, adjusting the angle of the solar panel as necessary.
- 5) Test the light to ensure the connection is sound. Note: this may take some time for the solar panel to charge the battery sufficiently.

### Applications

Outdoor areas, including walkways, building entrances, and loading areas

