

# WPF SERIES

## LED ROUND CUTOFF WALL PACK



- ✓ Die-Cast Aluminum Housing
- ✓ AC LED DOB Technology
- ✓ Corrosions Resistant Powdercoat
- ✓ UL, DLC Certified
- ✓ IP65 Weatherproof Rating

### Nominal Specifications

#### LifeLux™ PRO Rating

Pro

#### Power

50W, 100W

#### Voltage

100-277V AC- AC DOB LED

#### Lumen Output

112 lm/W

#### Design Life

100,000 hrs

#### Beam Angle

Type 3, 5 Optic

#### CRI

>80

#### Power Factor

>0.90

#### Color Temperature

30K, 35K, 40K, 50K

#### Certifications

UL, DLC, CE, RoHS

#### IP Rating

IP65

#### Dimensions

50W - 12.2" x 11.8" x 6.3" - 5 lbs

100W - 12.2" x 11.8" x 6.3" - 5.5 lbs

#### Warranty

10 Year Manufacturers Limited Warranty

### ORDERING DATA: Per chart below

Example: USALED-WPF-45-30K-EM

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model WPF	Wattage 50 = 50W 100 = 100 W	Color Temperature 30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	Options EM = Emergency Backup  OS = Occupancy Sensor

Model #	Wattage	CCT	Nominal Lumen Output
WPA-50	50W	3000K, 3500K, 4000K, 5000K	5,800 lm
WPA-100	100W	3000K, 3500K, 4000K, 5000K	11,200 lm

### Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires, placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, making sure the electric connection is sound, and that the photocell is operating correctly.

### APPLICATIONS

Outdoor Areas, Parking Garages, Building Entrances

