



PT-SQR SERIES

LED POST TOP

- ✓ Lightweight with a sleek appearance
- ✓ IP 65 Weather Rating
- ✓ DLC, ETL, and RoHS certified
- ✓ No Mercury and No Filament to burn out

Nominal Specifications

LifeLux™ STD Rating

Power

20W, 35W, 50W, 100W

Voltage

100-277V

Lumen Output

120 Lm/W

Color Temperature

3000K, 4000K, 5000K

Beam Angle

Type 5 Wide, Medium and Narrow

Lens

Clear

CRI

>75

Power Factor

>0.90

Warranty

5 Year Manufacturers Limited Warranty

Weather Rating

IP65

CERTIFICATIONS

DLC, ETL, RoHS

DIMENSIONS

14" x 14" x 30"

FEATURES

- No Mercury
- Dark Sky compliant
- No filament to burn out

ORDERING DATA: Per chart below

Example : USALED-PT-SQR-35-3000K

XXXXXX	XXXXXX	XXXXXX	XXXXXX
USALED	Model PT-SQR	Wattage 20 = 20W 35 = 35W 50 = 50W 100 = 100W	Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K
Model #	Wattage	CCT	Nominal Lumen Output
USALED-SQR-20	20W	3000K, 4000K, 5000K	2600 lm
USALED-SQR-35	35W	3000K, 4000K, 5000K	4550 lm
USALED-SQR-50	50W	3000K, 4000K, 5000K	6500 lm
USALED-SQR-100	100W	3000K, 4000K, 5000K	13000 lm

Installation Summary: (Detailed Instructions provided with Product)

- 1) Turn off power to existing fixture or junction box.
- 2) Disconnect and remove existing fixture if there is one.
- 3) Open the post top, locating the wires, and threading them through the exit hole.
- 4) Open junction box and locate corresponding wires.
- 5) Connect the corresponding wires on the fixture to the power source.
- 6) Close the junction box and secure the fixture into place.
- 7) Attach the light to the post and secure.
- 8) Test the light to ensure the electrical connection is sound.

APPLICATIONS

Post Tops in neighborhoods, building complexes, courtyards, and public parks.

