

CPB SERIES LED Canopy Light

- ✓ Over 15 Optical Lenses for any application
- ✓ ETL, DLC, and CE certified
- ✓ Modular Design permits Easy Installation
- ✓ Corrosion Resistant Powdercoat
- ✓ 70,000 Hour Rated Lifetime
- ✓ IP 67 Weatherproof Rating



Nominal Specifications

LifeLux™ STD Rating

Power

60W, 80W, 90W, 120W, 150W, 160W

Voltage

100-277V or 347-480V

Lumen Output

135 Lm/W

Color Temperature

3000K, 4000K, 5000K

Weather Rating

IP 67

Design Life

70,000 hrs

Beam Angle

Type 5 Wide, Medium, Narrow

CRI

>70

Power Factor

>0.95

Warranty

5 Year Manufacturers Limited Warranty

Certifications

ETL, DLC, CE

Dimensions

60W-120W - 9.5" x 14.2" x 4.9" - 8.5 lbs

150W - 14.2" x 14.2" x 4.9" - 12.1 lbs

160W - 11.9" x 16.3" x 4.85" - 10.5 lbs

ORDERING DATA: Per chart below

Example : USALED-CPB-60-40K-XX

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model CPB	Wattage 60 = 60W 80 = 80W 90 = 90W 120 = 120W 150 = 150W 160 = 160W	Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K	Options 0-10V Dimming = Blank 480 = 347-480V Driver

APPLICATIONS

Gas Station Canopy, Softs, Low Bay Mount Surface

Features

- Philips Programmable Driver





Installation Summary: (Detailed Instructions provided with Product)

- 1) Turn off Power.
- 2) Disconnect the existing fixture and remove.
- 3) Connect the wire leads to the fixture tail, securing as necessary.
- 4) Secure the light into place using the mounting screws.
- 5) Test light to ensure the electrical connection is sound.

Model #	Wattage	CCT	Nominal Lumen Output
USALED-CPB-60	60W	3000K, 4000K, 5000K	8,052 lm
USALED-CPB-80	80W	3000K, 4000K, 5000K	9,984 lm
USALED-CPB-90	90W	3000K, 4000K, 5000K	11,745 lm
USALED-CPB-120	120W	3000K, 4000K, 5000K	15,340 lm
USALED-CPB-150	150W	3000K, 4000K, 5000K	19,035 lm
USALED-CPB-160	160W	3000K, 4000K, 5000K	20,280 lm