

LED PLVAB

LED Vertical PL - Bypass



- ✓ Type A+B, Internal 120-277V Driver
- ✓ Die Cast Aluminum Heat Sink
- ✓ 50,000 Hour Rated Lifetime
- ✓ UL, FCC, & DLC Certified
- ✓ Vertical Configuration
- ✓ 5 Year Limited Manufacturers Warranty

Nominal Specifications

LifeLux™ Rating ECO

Power

25W

Voltage

120V

Lumen Output

85 Lm/W

Color Temperature

2400K, 2700K, 3000K

Beam Angle

120

CRI

>80

Power Factor

0.9

Certifications

Energy Star, UL, FCC

Dimensions

2.99"x3.78"

Warranty

5 Year Manufacturers Limited Warranty

Design Lifetime

50,000 hours

ORDERING DATA: Per chart below

Example: USALED-PLVA-12-27K-Y-XX-XX

XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX
Series	Wattage	Color Temperature	Ballast Bypass	Voltage	Dimming
USALED-PLHAB	12 = 25W	27K = 2700K 30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	Y = Yes N = No	Blank = 120V	Dimmable = Blank

Model #	Wattage	CCT	Nominal Lumens	Average Lifetime
USALED-PLHAB-12	12W	2700K, 3000K, 4000K	1,100 Lm	50,000 Hours

