



PTB Series LED Post Top Light

- ✓ 360 Degree Beam Angle
- ✓ UL, DLC, CE, Energy Star and FCC Certified
- ✓ Multiple Base Sizes for Universal Compatibility
- ✓ Cylindrical Design Allows For Light to Hit All Surrounding Area
- ✓ 50,000 Hours Design Life
- ✓ 5 Year Manufacturers Limited Warranty

Nominal Specifications

LifeLux™ STD Rating

Power

12W, 18W, 27W, 36W, 45W, 54W, 63W, 80W, 100W, 120W

Voltage

AC100-277V

Lumen Output

150 Lm/W

Color Temperature

2700K, 3000K, 4000K, 5000K

Design Life

50,000 hrs

Beam Angle

360 Deg

CRI

>80

Power Factor

>0.90

Certifications

UL, Energy Star, DLC, FCC, CE

Dimensions

Variable

Warranty

5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below

Example : USALED-PTB-D1-E26-40K

| xxxxxx | xxxxxx | xxxxxx | xxxxxx | xxxxxx | xxxxxx |
|--------|--------|----------|----------|-------------|-------------------|
| Series | Model | Wattage | Dimmable | Base | Color Temperature |
| USALED | PTB | 12 = 12W | D1 = No | E26 = E26 | 27K = 2700K |
| | | 18 = 18W | D2 = Yes | E29 = E29 | 30K = 3000K |
| | | 27 = 27W | | EX39 = EX39 | 40K = 4000K |
| | | 36 = 36W | | | 50K = 5000K |
| | | 45 = 45W | | | |
| | | 54 = 54W | | | |

| Model # | Base | Wattage | CCT | Nominal Lumen Output |
|---------------|----------------|---------|----------------------------|----------------------|
| USALEDPTB-12 | E26, E29, EX39 | 12W | 2700K, 3000K, 4000K, 5000K | 1,800 lm |
| USALEDPTB-18 | E26, E29, EX39 | 18W | 2700K, 3000K, 4000K, 5000K | 2,700 lm |
| USALEDPTB-27 | E26, E29, EX39 | 27W | 2700K, 3000K, 4000K, 5000K | 4,050 lm |
| USALEDPTB-36 | E26, E29, EX39 | 36W | 2700K, 3000K, 4000K, 5000K | 5,400 lm |
| USALEDPTB-45 | E26, E29, EX39 | 45W | 2700K, 3000K, 4000K, 5000K | 6,750 lm |
| USALEDPTB-54 | E26, E29, EX39 | 54W | 2700K, 3000K, 4000K, 5000K | 8,100 lm |
| USALEDPTB-63 | E26, E29, EX39 | 63W | 2700K, 3000K, 4000K, 5000K | 9,450 lm |
| USALEDPTB-80 | E26, E29, EX39 | 80W | 2700K, 3000K, 4000K, 5000K | 12,000 lm |
| USALEDPTB-100 | E26, E29, EX39 | 100W | 2700K, 3000K, 4000K, 5000K | 15,000 lm |
| USALEDPTB-120 | E26, E29, EX39 | 120W | 2700K, 3000K, 4000K, 5000K | 18,000 lm |

FEATURES

- Multiple base sizes for universal compatibility

APPLICATIONS

Street Lights, Post Tops

