



WPE SERIES

LED CLASSIC MINI WALL

The WPE Series Classic Mini Wall Pack is the best solution to any outdoor or indoor wall pack lighting where a low profile is desired. The Classic Mini Wall Pack lighting solution works beyond all expectations of efficient lighting and is visually appealing.

Nominal SPECIFICATIONS

Power 17W, 25W	Beam Angle Type 5, Wide, Medium, Narrow
Voltage 100-277V	CRI >70
Lumen Output 90Lm/W	Power Factor >0.90
Color Temperature 4000K, 5000K	Warranty 10 Year Manufacturers Limited Warranty
Design Life 60,000 hrs	

CERTIFICATIONS

UL, DLC

DIMENSIONS

8.375" x 5.5" x 3.5" - 4.4 lbs

APPLICATIONS

Outdoor Areas

ORDERING DATA: Per chart below

Example : USALED-WPE-25W-40K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model WPE	Wattage 17 = 17W 25 = 25W	Color Temperature 40K = 4000K 50K = 5000K	Options EM = Emergency Backup P = Photocell OS = Occupancy Sensor

Model #	Wattage	CCT	Nominal Lumen Output
WPE-15	15W	4000K, 5000K	1,650 lm
WPE-25	17W	4000K, 5000K	2,100 lm

Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires , placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, making sure the electric connection is sound, and that the photocell is operating correctly.