

WSB Series LED WALL SCONCE



- ✓ Die-Cast Cold Rolled Steel Housing
- ✓ High Transmission Glass For Optimal Light Distribution
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ ETL, UL & Energy Star Certified
- ✓ 50,000 Hour Rated Lifetime
- ✓ Perfect For Hotels, Lobbies & Other Indoor Areas

Nominal Specifications

LifeLux™ STD Rating

Power
15W

Voltage
100-277V

Lumen Output
77 Lm/W

Color Temperature

3000K, 3500K, 4000K

Design Life
50,000 hrs

CRI
>80

Power Factor
>0.90

Certifications

ETL, UL, Energy Star

Dimensions

11.5" x 10.3" x 4.2"

Warranty

5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below

Example : USALED-WSB-15W-40K

XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX
USALED	Model WSB	Size 11.5 = 11.5"	Wattage 15 = 15W	Color Temperature 30K = 3000K 35K = 3500K 40K = 4000K	Options EM = Emergency Battery Backup

Model #	Size	Wattage	CCT	Nominal Lumen Output
USALED-WSB-16	11.5"	15W	3000K, 3500K, 4000K	1,150 lm

Installation Summary:

- 1) Locate power source and shut off.
- 2) Open the fixture and locate the wires, locating the corresponding wires going to the power source.
- 3) Connect the wires, making sure the connection is secure.
- 4) Position the fixture in place, making sure that it is level, and secure as necessary.
- 5) Test the light, making sure the electric connection is sound.

Applications:

Interior lighting, such as hallways, entryways, and lobbies

