



DK SERIES LED DOCK LIGHT

- ✓ Perfect For Loading Bays & Cargo Units
- ✓ IP65 Weatherproof Rating
- ✓ UL, DLC & ETL Certified
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ 50,000 Hour Rated Lifetime

Nominal Specifications

LifeLux™ STD Rating

Power
20W, 30W, 40W, 50W

Voltage
100-277 V

Lumen Output
100 Lm/W

Color Temperature
3000K, 4000K, 5000K, 6500K

Design Life
50,000 hrs

CRI
>80

Power Factor
>0.9

Warranty
5 Year Manufacturers Limited Warranty

Beam Angle
25 Deg, 40 Deg, 60 Deg

Certifications

UL, DLC, ETL

Dimensions

Fixture - 7" Diameter x 5" Depth - 3.3 lbs.

Arm - 40" or 60"

Weather Rating

IP65

Applications

Loading Bays and Cargo Units

ORDERING DATA: Per chart below

Example : USALED-DK-16W-50K-A

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model DK	Wattage 20 = 20W 30 = 30W 40 = 40W 50 = 50W	Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K 65K = 6500K	Options A = Wall Mount Arm

Model #	Wattage	CCT	Nominal Lumen Output
USALED-DK-20	20W	3000K, 4000K, 5000K, 6500K	1,800 lm
USALED-DK-30	30W	3000K, 4000K, 5000K, 6500K	2,700 lm
USALED-DK-40	40W	3000K, 4000K, 5000K, 6500K	3,600 lm
USALED-DK-50	50W	3000K, 4000K, 5000K, 6500K	4,500 lm

Installation Summary:

- 1) Locate power source near desired location and shut off power.
- 2) Open junction box and locate wires corresponding to fixture wires.
- 3) Connect wires to fixture and secure within the junction box.
- 4) Attach fixture to desired location, either by the adjustable arm or with direct-mount bolts.
- 5) Adjust angle of the fixture as needed.
- 6) Test light to ensure the electrical connection is sound.



Note : Suitable for Dry and Damp Locations