



# GLF SERIES LED ORNAMENTAL FIXTURE

- ✓ UL, FCC, ETL Certified
- ✓ IP67 Weatherproof Rating
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ 20-100 Watt Power Range
- ✓ Unique Architectural Design

**Nominal Specifications**

**LifeLux™ STD Rating**

**Power**  
20W, 35W, 50W, 100W

**Voltage**  
100-277V

**Lumen Output**  
120 Lm/W

**Color Temperature**  
3000K, 4000K, 5000K

**Beam Angle**

Type 5 Wide, Medium and Narrow

**CRI**  
>80

**Power Factor**  
>0.90

**Weather Rating**  
IP65

**Certifications**

UL, FCC, ETL

**Dimensions**

16.5" Diameter x 13" Height - 17.9 lbs (Fixture)

19" Width x 30" Height - 4.9 lbs (Arm)

**Warranty**

5 Year Manufacturers Limited Warranty

**ORDERING DATA: Per chart below**

Example : USALED-GLF-20-30K

xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model GLF	Wattage 20 = 20W 35 = 35W 50 = 50W 100 = 100W	Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K

Model #	Wattage	CCT	Nominal Lumen Output
USALED-GLF-20	20W	3000K, 4000K, 5000K	2,400 lm
USALED-GLF-35	35W	3000K, 4000K, 5000K	4,200 lm
USALED-GLF-50	50W	3000K, 4000K, 5000K	6,000 lm
USALED-GLF-100	100W	3000K, 4000K, 5000K	12,000 lm

**Installation Summary:** ( Detailed Instructions provided with Product)

- 1) Turn off power to existing fixture or junction box.
- 2) Disconnect and remove existing fixture if there is one.
- 3) Open the post top, locating the wires, and threading them through the exit hole.
- 4) Open junction box and locate corresponding wires.
- 5) Connect the corresponding wires on the fixture to the power source.
- 6) Close the junction box and secure the fixture into place.
- 7) Attach the light to the post and secure.
- 8) Test the light to ensure the electrical connection is sound.

**APPLICATIONS**

Architectural Post Tops, Walkway Lights

