



CPE SERIES LED Canopy Light

- ✓ 5 KV Surge Protection
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ ETL and DLC Certified
- ✓ Powder Coated Aluminum Housing
- ✓ Rated Operating Temperature of -40° to 130° F

Nominal Specifications

LifeLux™ STD Rating
Power
 20W, 30W, 40W, 75W
Voltage
 100-277V OR 347-480V
Lumen Output
 135 Lm/W
Color Temperature
 4000K, 5000K

Design Life
 78,000 hrs
Beam Angle
 Type 5 Wide, Medium, Narrow
CRI
 >80
Power Factor
 >0.95
Weather Rating
 IP65

Certifications
 ETL, DLC, RoHS
Dimensions
 18" x 18" x 9.25" - 10.5 lbs
Applications
 Gas Station Canopy, Sofits, Low Bay
 Surface Mount
Warranty
 5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below
 Example : USALED-CPE-40W-40K

XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX
USALED	Model CPE	Wattage 20 = 20W 30 = 30W 40 = 40W 75 = 75W	Color Temperature 40K = 4000K 50K = 5000K	Options EM = Emergency Battery Pack OC = Occupancy Sensor P = Photocell

Model #	Wattage	CCT	Nominal Lumen Output
USALED-CPE-20	20W	4000K, 5000K	2,700 lm
USALED-CPE-30	30W	4000K, 5000K	4,050 lm
USALED-CPE-40	40W	4000K, 5000K	5,400 lm
USALED-CPE-75	75W	4000K, 5000K	10,125 lm

Installation Summary: (Detailed Instructions provided with Product)

- 1) Turn off Power.
- 2) Disconnect the existing fixture and remove.
- 3) Connect the wire leads to the fixture tail, securing as necessary.
- 4) Secure the light into place.
- 5) Test Light to ensure the electrical connection is sound.

