



# WPR SERIES LED ADJUSTABLE WALL

The WPR Series Adjustable Wall Pack Fixture is the best solution to any outdoor or indoor wall pack lighting where a unique angle is needed. Included with this fixture is an easy-to-use mounting plate. This fixture works beyond all expectations of efficient lighting to provide a visually appealing lighting

## NOMINAL SPECIFICATIONS

<b>Power</b> 30W, 40W, 60W, 80W	<b>CRI</b> >70	<b>Dimensions</b> 30W-40W - 9.15" x 5.4" x 5.2" 60W-80W - 9.15" x 8.85" x 5.2"
<b>Voltage</b> 120-277V	<b>Power Factor</b> >0.95	<b>Certifications</b> UL, DLC
<b>Lumen Output</b> 130 Lm/W	<b>Warranty</b> 5 Year Manufacturers Limited Warranty	<b>Weather Rating</b> Wet location rated
<b>Color Temperature</b> 3000K, 4000K, 5000K	<b>Beam Angle</b> 15, 25, 30, 40, 60, 90, 120 degrees	
<b>Design Life</b> 50,000 hrs		

## ORDERING DATA: Per chart below

Example : USALED-WPR-40-50K-EM

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model WPR	Wattage 30 = 30W 40 = 40W 60 = 60W 80 = 80W	Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K	Options EM = Emergency Battery Backup

Model #	Wattage	CCT	Nominal Lumen Output
WPR-30	30W	3000K, 4000K, 5000K	3,900 lm
WPR-40	40W	3000K, 4000K, 5000K	5,200 lm
WPR-60	60W	3000K, 4000K, 5000K	7,800 lm
WPR-80	80W	3000K, 4000K, 5000K	10,400 lm

## Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Attach the mounting plate to the desired surface using screws or bolts, depending on the material.
- 3) Position and attach the fixture to the mounting plate .

Note : Suitable for Dry and Damp Locations