

WPA SERIES

LED ROUND CUTOFF WALL PACK



- ✓ Die-Cast Aluminum Housing
- ✓ Corrosions Resistant Powdercoat
- ✓ Multiple Exterior Housing Color Options
- ✓ UL, DLC, CE, & RoHS Certified
- ✓ IP65 Weatherproof Rating

| | | |
|--|---|--|
| Nominal Specifications LifeLux™ STD Rating Length 14" Power 30W, 60W, 80W Voltage 100-277V AC Lumen Output 130 Lm/W | Design Life 60,000 hrs Beam Angle Type 3 Optic CRI >70 Power Factor >0.90 Color Temperature 3000K, 4000K, 5000K | Certifications UL, DLC, CE, RoHS IP Rating IP65 Dimensions 30W - 12.8" x 7.5" x 6.3" - 12.7 lbs 60W-80W - 16.3" x 9.7" x 9.1" - 13.54 lbs Warranty 5 Year Manufacturers Limited Warranty |
|--|---|--|

ORDERING DATA: Per chart below
 Example: USALED-WPA-45-30K-EM

| xxxxxx | xxxxxx | xxxxxx | xxxxxx | xxxxxx |
|--------|--------------|---|--|---|
| USALED | Model WPA | Wattage 30 = 30W 60 = 60W 80 = 80W | Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K | Options EM = Emergency Backup OS = Occupancy Sensor |

| Model # | Wattage | CCT | Nominal Lumen Output |
|---------|---------|---------------------|----------------------|
| WPA-30 | 30W | 3000K, 4000K, 5000K | 4,030 lm |
| WPA-60 | 60W | 3000K, 4000K, 5000K | 8,052 lm |
| WPA-80 | 80W | 3000K, 4000K, 5000K | 9,984 lm |

Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires, placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, making sure the electric connection is sound, and that the photocell is operating correctly.

APPLICATIONS

Outdoor Areas, Parking Garages, Building Entrances

