



# ARJ Series

- ✓ Die-Cast Aluminum Housing
- ✓ 50,000 Design Life Hours
- ✓ Corrosions Resistant Powdercoat
- ✓ UL, DLC Certified
- ✓ IP65 Weatherproof Rating

**Nominal Specifications**

**LifeLux™ PRO Rating**

Pro

**Power**

40W, 75W, 100W, 120W, 150W, 200W, 240W, 320W

**Voltage**

100-277V

347-480V

**Lumen Output**

140 Lm/W

**Design Life**

50,000 hrs

**Beam Angle**

120 Deg

**CRI**

>80

**Power Factor**

>0.9

**Color Temperature**

3000K, 4000K, 5000K

**Certifications**

ETL, UL, DLC

**IP Rating**

IP65

**Dimensions**

**Warranty**

5 Year Manufacturers Limited Warranty

**ORDERING DATA: Per chart below**

Example: USALED-ARJ-120A-40K-3-B-Z1-D1

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
Series	Model	Wattage	Voltage	Color Temperature	Optics	Finish	Mounting	Options
USALED	ARJ	40 = 40W 75 = 75W 100 = 100W 120 = 120W 150 = 150W 200 = 200W 240 = 240W 320 = 320W	A = 100-277V B = 277-480V	30K = 3000K 40K = 4000K 50K = 5000K	1 = Type 1 2 = Type 2 3 = Type 3 4 = Type 4 5 = Type 5	B = Black W = White D = Dark Bronze G = Gray	Z1 = SFA Z2 = SFB Z3 = SFC Z4 = SP Z5 = RP Z6 = TRU Z7 = SLI Z8 = ASM Z9 = ASL Z10 = ARM Z11 = ARL Z12 = AON	D1 = Photocell D2 = Surge Protection D4 = Motion Sensor D5 = D1 + D4 C1 = Custom N = w/o Sensor

Model #	Wattage	CCT	Nominal Lumen Output
USALED-ARJ	40	3000K, 4000K, 5000K	5,600 Lumens
	75	3000K, 4000K, 5000K	10,500 Lumens
	100	3000K, 4000K, 5000K	14,000 Lumens
	120	3000K, 4000K, 5000K	16,800 Lumens
	150	3000K, 4000K, 5000K	21,000 Lumens
	200	3000K, 4000K, 5000K	28,000 Lumens
	240	3000K, 4000K, 5000K	33,600 Lumens
	320	3000K, 4000K, 5000K	44,800 Lumens

**APPLICATIONS**

Outdoor Areas, Parking Garages, Building Entrances

