



TRMA Select Series LED Troffer

- ✓ UL, DLC, FCC, CE, RoHS Certified
- ✓ IP40 Weatherproof Rating
- ✓ Color & Power Tunable Switch
- ✓ Durable Plastic & Polycarbonate Housing
- ✓ Lightweight Design
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ 50,000 Hour Rated Lifetime

Nominal Specifications

LifeLux™ STD Rating

Power

20W, 25W, 30W, 35W Adjustable (2 x 2)
35W, 40W, 45W, 50W Adjustable (2x4)

Lumen Output

125 Lm/W

Color Temperature

3000K-5000K Adjustable

Design Life

50,000 hrs

Beam Angle

120 Deg

CRI

>80

Power Factor

>0.95

Voltage

AC 100-277V, 120-347V

Certifications

UL, DLC, FCC, CE, RoHS

Dimensions

2 x 2 - 23.75" x 23.75" x 3.0" - 5.1 lbs
2 x 4 - 47.75" x 23.75" x 3.0" - 8.6 lbs

Warranty

5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below

Example : USALED-TRMA22-20-DM-02

XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX
USALED	Size TRMA22 = 2x2 TRMA24 = 2x4	Wattage 35 = 20W / 25W / 30W / 35W 50 = 35W / 40W / 45W / 50W	CCT Blank = 3000K 3500K 4000K	Options D = Dimmable DM = Dim + Motion Sensor 120-277V DE = Dim + EM Backup 120-277V ME = Dim + Motion Sensor + EM Backup 100-277V DH = Dim + 120-347V	02


APPLICATIONS

Offices, Retail Stores, Hospitals, Hotels, Restaurants,
Grocery Stores, Commercial Buildings, etc

FEATURES

- Plastic Housing
- Aluminum Ballast Pan
- Glare-Free Frosted Lens
- Fire Safety Aircraft Cable





Installation Summary: (Detailed Instructions provided with Product)

1. Turn off Power.
2. Disconnect the existing fixture and remove.
3. Open the driver cover on the backside of the troffer with a screwdriver.
3. Connect the wire leads to the driver, securing as necessary.
4. Close and reattach the driver cover.
5. Secure troffer into place.
6. Test light to ensure the electrical connection is sound.
7. Make sure the remote is synced to the light and is operating correctly.

Model #	Length	Wattage	CCT	Nominal Lumen Output
USALED-TRMA22	2 ft	20W, 25W, 30W, 35W Adjustable	3000K, 3500K, 4000K, 5000K Adjust- able	2,500-4,375 lm 4,375-6,250 lm
USALED-TRMA24	4 ft	35W, 40W, 45W, 50W Adjustable	3000K, 3500K, 4000K, 5000K Adjust- able	