

WPB SERIES

LED ARCHITECTURAL FULL CUTOFF WALLPACK



- ✓ **DLC & UL Certified**
- ✓ **Sealed Die-Cast Housing**
- ✓ **Head Tilts Up To 20 Degrees**
- ✓ **Rated Operating Temperature of -40° To 113° Fahrenheit**
- ✓ **50,000 Hour Rated Lifetime**
- ✓ **Photocell Optional For Certain Applications**

Nominal Specifications LifeLux™ STD Rating Power 30W, 40W, 70W, 90W Voltage 100-277V Lumen Output 110 Lm/W	CRI >70 Power Factor >0.90 Warranty 5 Year Manufacturers Limited Warranty Design Life >50,000 hrs	Beam Angle 120 Deg Certifications DLC, UL Dimensions 30W-40W - 9" x 7" x 4" - 5.7 lbs 70W-90W - 12" x 10" x 6" - 13.2 lbs Applications All Outdoor Areas, Including Moist Areas
--------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ORDERING DATA: Per chart below
 Example : USALED-WPB-20W-40K-PC

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model	Wattage	Color Temperature	Options
	WPB-30	30 = 30W	40K = 4000K	PC = Photocell
	WPB-40	40 = 40W	50K = 5000K	
	WPB-70	70 = 70W		
	WPB-90	90 = 90W		

Model #	Wattage	CCT	Nominal Lumen Output
WPB-30	30 = 30W	4000K, 5000K	3,000 lm
WPB-40	40 = 40W	4000K, 5000K	4,500 lm
WPB-70	70 = 70W	4000K, 5000K	7,500 lm
WPB-90	90 = 90W	4000K, 5000K	9,700 lm

FEATURES

- Photocell control
- Integrated Junction Box
- Adjustable angle

Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires , placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, ensure the electric connection is sound, and the photocell is operating correctly.

