



WPC SERIES

LED CLASSIC FULL CUTOFF WALL PACK

- ✓ 60,000 Hour Rated Lifetime
- ✓ Full Cutoff Compliance For Dark Sky
- ✓ Rated Operating Temperature From -40° To 113° Fahrenheit
- ✓ Replaces 100-400 Watt Metal Halide
- ✓ Emergency Backup & Occupancy Sensor Optional

Nominal Specifications

LifeLux™ STD Rating

Length

14"

Power

27W, 45W, 70W, 90W, 135W

Voltage

100-277V AC

Lumen Output

111 Lm/W

Design Life

60,000 hrs

CRI

>80

Power Factor

>0.90

Color Temperature

3000K, 4000K, 5000K

Certifications

UL, DLC

Dimensions

27W-70W - 14.21" x 8.78" x 9.25" - 12.1 lbs

90W-135W - 18.1" x 9.75" x 10.8" - 13.2 lbs

Warranty

5 Year Manufacturers Limited Warranty

Beam Angle

Type 3 Optic

ORDERING DATA: Per chart below

Example: USALED-WPC-45-30K-EM

XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX
USALED	Model WPC	Wattage 27 = 27W 45 = 45W 70 = 70W 90 = 90W 135 = 135W	Color Temperature 30K = 3000K 40K = 4000K 50K = 5000K	Options EM = Emergency Backup OS = Occupancy Sensor

Model #	Wattage	CCT	Nominal Lumen Output
WPC-27	27W	3000K, 4000K, 5000K	2,970 LM
WPC-45	45W	3000K, 4000K, 5000K	4,950 lm
WPC-70	70W	3000K, 4000K, 5000K	7,750 lm
WPC-90	90W	3000K, 4000K, 5000K	9,500 lm
WPC-135	135W	3000K, 4000K, 5000K	14,000 lm

Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires, placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, making sure the electric connection is sound, and that the photocell is operating correctly.

Applications

Outdoor Areas, Parking Garages, Building Entrances

