



USALED SLR C

Solar-Integrated LED

- ✓ UL & DLC Certified
- ✓ Rotatable Solar Panel
- ✓ Lithium Battery Rated For 2000 Cycles Of Charge & Discharge
- ✓ Rated Operating Temperature Of -4° To 140° Fahrenheit
- ✓ 50,000 Hour Rated Lifetime

Nominal Specifications LifeLux™ STD Rating Power 4W, 8W, 12W Voltage 5V Solar Panel Color Temperature 3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K, 6500K	Lumen Output 165 lm/W Design Life 50,000 hrs CRI >70 Power Factor >0.90 Warranty 3 Year Manufacturers Limited Warranty	Certifications UL, DLC Weather Rating IP65 Dimensions 19.6" x 7.5" x 11.8" (Fixture) 4W - 14" x 9.25" - 15.4 lbs (Panel) 8W - 14" x 20" - 23.1 lbs (Panel) 12W - 14" x 25" - 30.9 lbs (Panel) Mounting Height 9'-20'
---	--	--

ORDERING DATA: Per chart below
 Example: USALED-SLR-C-9-6-30K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model SLR-C	Panel Width 9 = 9.25" 20 = 20" 25 = 25"	Wattage 4 = 4W 8 = 8W 12 = 12W	Color Temperature 3000K 3500K 4000K 4500K 5000K 5500K 6000K 6500K

Model #	Wattage	CCT	Nominal Lumen Output
SLR-C-4	4W	3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K, 6500K	720 lm
SLR-C-8	8W	3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K, 6500K	1,440 lm
SLR-C-12	12W	3000K, 3500K, 4000K, 4500K, 5000K, 5500K, 6000K, 6500K	1,800 lm

Installation Summary: (Detailed Instructions provided with Product)

- 1) Set the mounting pole to the appropriate height.
- 2) Locate the wires coming out of the fixture, locating the corresponding wires on the solar panel.
- 3) Connect the corresponding wires and secure as necessary.
- 4) Secure the fixture to the top of the pole, adjusting the angle of the solar panel as necessary.
- 5) Test the light to ensure the connection is sound. Note: this may take some time for the solar panel to charge

Applications

Outdoor areas, including walkways, building entrances, and loading areas

