



WPV Series

- ✓ Die-Cast Aluminum Housing
- ✓ 50,000 Design Life Hours
- ✓ Corrosions Resistant Powdercoat
- ✓ UL, DLC Certified
- ✓ IP65 Weatherproof Rating

Nominal Specifications

LifeLux™ PRO Rating

Pro

Power

20W, 30W

Voltage

100-277V

Lumen Output

100 Lm/W

Design Life

50,000 hrs

Beam Angle

120 Deg

CRI

>80

Power Factor

>0.90

Color Temperature

3000K, 4000K, 5000K

Certifications

UL, DLC

IP Rating

IP65

Dimensions

8.54" x 8.63" x 9.75"

Warranty

5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below

Example: USALED-WPV-20-D1

xxxxxx	xxxxxx	xxxxxx	xxxxxx
Series USALED	Model WPV	Wattage 20 = 20W 30 = 30W	Dimming D1 = Non-Dim

Model #	Wattage	CCT	Nominal Lumen Output
USALED-WPT	20W	3000K, 4000K, 5000K	2,000 Lumens
	30W	3000K, 4000K, 5000K	3,000 Lumens

APPLICATIONS

Outdoor Areas, Parking Garages, Building Entrances

Installation Summary:

- 1) Locate power source and shut off. Be sure that no moisture is interfering with the wiring.
- 2) Open the fixture using a screwdriver, and locate the corresponding wires going to the power source.
- 3) Having already removed the junction box, position and attach it to the mounting surface using screws or bolts, depending on the material.
- 4) Connect the wires, placing them within the junction box.
- 5) Replace the screws and reassemble the fixture.
- 6) Test the light, making sure the electric connection is sound, and that the photocell is operating correctly.

