



CPD SERIES LED Canopy Light

- ✓ Replaces HPS and Metal Halide
- ✓ 70,000 Hour Rated Lifetime
- ✓ ETL, DLC and UL Certified
- ✓ 5 Year Manufacturer Warranty
- ✓ Sealed Die-Cast Housing for Indoor and Outdoor Use

Nominal Specifications
LifeLux™ STD Rating

Power
30W, 45W, 60W

Voltage
100-277V OR 347-480V

Lumen Output
130 Lm/W

Color Temperature
4000K, 5000K

Beam Angle
Type 5 Wide, Medium, Narrow

CRI
>75

Power Factor
>0.90

Design Life
70,000 hrs

Certifications
ETL,DLC,UL

Dimensions
11" Diameter x 3" Depth

ORDERING DATA: Per chart below
Example : USALED-CPD-40W-40K

Model #	Wattage	CCT	Nominal Lumen Output
USALED-CPD-30	30W	4000K, 5000K	3,800 lm
USALED-CPD-45	45W	4000K, 5000K	5,500 lm
USALED-CPD-60	60W	4000K, 5000K	7,600 lm

Model #	Wattage	CCT	Nominal Lumen Output
USALED-CPD-30	30W	4000K, 5000K	3,800 lm
USALED-CPD-45	45W	4000K, 5000K	5,500 lm
USALED-CPD-60	60W	4000K, 5000K	7,600 lm

Installation Summary: (Detailed Instructions provided with Product)

- 1) Turn off Power.
- 2) Disconnect the existing fixture and remove.
- 3) Connect the wire leads to the fixture tail, securing as necessary.
- 4) Secure the light into place using the mounting screws.
- 5) Test light to ensure the electrical connection is sound.

APPLICATIONS

Gas Station Canopy, Sofits, Low Bay Surface Mount

