



# SC SERIES

## LED SECURITY LIGHT

- ✓ Replaces 100 - 175 Watt Metal Halide Lights
- ✓ UL & DLC Certified
- ✓ Rated Operating Temperature Of -40° To 113° Fahrenheit
- ✓ 50,000 Hour Rated Lifetime
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ Suitable For Wet Locations

<b>Nominal Specifications</b>	<b>LifeLux™ STD Rating</b>	<b>Certifications</b>
<b>Power</b> 45W, 70W	<b>Design Life</b> 50,000 hrs	UL, DLC
<b>Voltage</b> 100-277V	<b>CRI</b> >80	<b>Dimensions</b> 18" x 8" x 5" - 8.2 lbs
<b>Lumen Output</b> 105 Lm/W	<b>Power Factor</b> >0.9	<b>Warranty</b> 5 Year Manufacturers Limited Warranty
<b>Color Temperature</b> 4000K, 5000K	<b>Housing Color Options</b> Dark Bronze & Silver Gray Powdercoat	

**ORDERING DATA: Per chart below**  
Example : USALED-SC-45W-50K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
Model	Wattage	Color Temperature	Options	
USALED	45 = 45W 70 = 70W	40K = 4000K 50K = 5000K	Blank = No features PC = Photocell	

Model #	Wattage	CCT	Nominal Lumen Output
USALED-SC-45	45W	4000K, 5000K	4,927 lm
USALED-SC-70	70W	4000K, 5000K	7,000 lm

**Installation Summary:** (Detailed Instructions provided with Product)

- 1) Turn off power to existing fixture or junction box.
- 2) Disconnect and remove existing fixture if there is one.
- 3) Open the security light, locating the wires, and threading them through the exit hole.
- 4) Secure the fixture to the bracket, and adjust as necessary, continuing to thread the wires through.
- 5) Open junction box and locate corresponding wires
- 6) Connect the corresponding wires on the fixture to the power source.
- 7) Close the junction box and secure the fixture and bracket into place.
- 9) Test the light to make sure the electrical connection is sound.

**Applications:**  
Loading Bays, Garages, Alleys

Kit Includes: Photocell

**Note : Suitable for Dry and Damp Locations**

