



LED PL SERIES

VERTICLE LED PL LAMP

The USALED Verticle PL lamp is a perfect solution for replcing recessed can lights. It can be run in Ballast Compatible, Bypass or Hybrid Mode.

Nominal SPECIFICATIONS

Power
6.5W, 7W, 9.5W, 11.5W

Voltage
100-277V

Lumen Output
80-120 Lm/W

Color Temperature
2700K, 3000K, 4000K

Base
G24/GX24, GX23

Design Life
40,000 hrs

Beam Angle
25 / 40 / 60 degrees

CRI
90

Power Factor
0.9

Warranty
3 Year Manufacturers Limited Warranty

CERTIFICATIONS
UL, DLC

Dimensions
5.2" x 3.5" - 0.2 lbs

ORDERING DATA: Per chart below

Example : USALED-PLV-7-40K-B

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model PLV	Wattage 6.5 = 6.5W 7 = 7W 9.5 = 9.5W 11.5 = 11.5W	Color Temp 27K = 2700K 30K = 3000K 40K = 4000K	Options B = Ballast Bypass C = Ballast Compatible H = Hybrid

APPLICATIONS

Office buildings, Apartment buildings

Kit Includes:

Installation Summary:



Note : Suitable for Dry and Damp Locations

Model #	Length	Wattage	CCT	Nominal Lumen Output
PLV	5.2"	6.5W	2700K, 3000K, 3500K, 4000K	600 lm
PLV	5.2"	7W	2700K, 3000K, 3500K, 4000K	600 lm
PLV	5.2"	9.5W	2700K, 3000K, 3500K, 4000K	1000 lm
PLV	5.2"	11.5W	2700K, 3000K, 3500K, 4000K	1100 lm