

# PNDT SERIES LED PENDANT LIGHT



- ✓ Multiple Exterior Housing Colors
- ✓ 50,000 Hour Rated Design Life
- ✓ 3 Year Limited Manufacturers Warranty
- ✓ Rated For Dry & Damp Locations
- ✓ Energy Star & UL Certified
- ✓ Perfect for Hallways & Offices
- ✓ High Lumen Efficiency At 100 Lm/W

**Nominal Specifications**

**LifeLux™ STD Rating**

**Power**

30W

**Voltage**

100-277V

**Lumen Output**

100 Lm/W

**Color Temperature**

2700K, 3000K, 4000K

**Design Life**

50,000 hrs

**CRI**

>80

**Power Factor**

>0.90

**Beam Angle**

120 degrees

**Certifications**

Energy Star, UL

**Dimensions**

12" Diameter x 12" Length

**Warranty**

3 Year Manufacturers Limited Warranty

**Applications:**

Hallway, Offices, Architectural appeal

**ORDERING DATA: Per chart below**

Example : USALED-PNDT-30-27K-R

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model LBP	Wattage 30 = 30W	Color Temperature 27K = 2700K 30K = 3000K 40K = 4000K	Finish Color R = Red G = Green Y = Yellow

Model #	Size	Wattage	CCT	Nominal Lumen Output
USALED-PNDT-30	12 inch	30W	4000K, 5000K	3,000 lm

**Installation Summary:**

- 1) Turn off power to existing fixture or junction box.
- 2) Disconnect and remove existing fixture if there is one.
- 3) Locate struts or beams to anchor the fixture to.
- 4) Secure the hanging wire through the fixture.
- 5) Open junction box and locate wires, locating the corresponding wires on the light.
- 6) Connect the corresponding wires on the fixture to the power source.
- 7) Close the junction box and secure.
- 8) Test the light to ensure the electrical connection is sound.

**Note : Suitable for Dry and Damp Locations**

