



# WSA Series LED WALL SCONCE

- ✓ Die-Formed Col-Rolled Steel Housing
- ✓ High Transmission Glass For Optimal Light Distribution
- ✓ 5 Year Limited Manufacturers Warranty
- ✓ 50,000 Hour Rated Lifetime
- ✓ UL, ETL, & Energy Star Certified
- ✓ Perfect For Hotels, Lobbies, Or Other Applications Indoors

**Nominal Specifications**

LifeLux™ STD Rating

**Power**

15W

**Voltage**

100-277V

**Lumen Output**

77 Lm/W

**Color Temperature**

2700K, 3000K, 3500K, 4000K

**Design Life**

50,000 hrs

**CRI**

>80

**Power Factor**

>0.90

**Certifications**

UL, ETL, Energy Star

**Dimensions**

10" x 7.2" x 4"

**Warranty**

5 Year Manufacturers Limited Warranty

**ORDERING DATA: Per chart below**

Example : USALED-WSA-15W-40K

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx
USALED	Model WSA	Size 10 = 10"	Wattage 15 = 15W	Color Temperature 30K = 3000K 35K = 3500K 40K = 4000K	Options EM = Emergency Battery Backup

Model #	Size	Wattage	CCT	Nominal Lumen Output
USALED-WSA-16	10"	15W	3000K, 3500K, 4000K	1,150 lm

**Installation Summary:**

- 1) Locate power source and shut off.
- 2) Open the fixture and locate the wires, locating the corresponding wires going to the power source.
- 3) Connect the wires, making sure the connection is secure.
- 4) Position the fixture in place, making sure that it is level, and secure as necessary.
- 5) Test the light, making sure the electric connection is sound.

**Applications**

Interior lighting, such as hallways, entryways, and lobbies

