



USALED-T8BA SERIES

**DOUBLE END POWERED
BALLAST BYPASS, TYPE B
DLC, UL, ETL LISTED**

Nominal SPECIFICATIONS
LifeLux™ STD Rating

Length
2ft, 3ft, 4ft

Power
9W ,12W ,15W

Voltage
100-277V

Lumen Output
150 Lm/W

Color Temperature
3000K, 3500K, 4000K, 5000K

Uplight >18%

Lens
Glare Free Frosted

Design Life
50,000 hrs

Beam Angle
280 degrees

CRI
>80

Power Factor
>0.90

Warranty
5 Year Manufacturers Limited Warranty

CERTIFICATIONS
UL, DLC, ETL

Base
G13 Bi-pin

DIMENSIONS
24" x 1" DIA
36"x1"DIA
48" x 1" DIA

Material of Construction
Glass

ORDERING DATA: Per chart below

Example : **USALED-T8BA-4G-12-40K-00**

xxxxxx	xxxxxx	xxxxxx	xxxxxx	xxxxxx	oo
USALED	Model T8BA	Length 2G = 4ft 3G = 3ft 4G= 4ft	Wattage 09 = 9W 12 = 12W 15 = 15W	Color Temp 30K = 3000K 35K = 3500K 40K = 4000K 50K = 5000K	OO

APPLICATIONS

Offices, Retail Stores, Hospitals, Grocery Stores, Utility Rooms, Industrial Settings, Stairwells, Commercial Buildings, Hotels, Restaurants